

ADJUSTING DEVICE

CROSS-REFERENCES TO RELATED APPLICATIONS

[0001] This application claims the priority of German Patent Application Serial No. 299 20 996.2, filed November 30, 1999, the subject matter of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] The present invention relates, in general, to an adjusting device, and more particularly to an adjusting device of a type including a lifting mechanism and a rotary drive having an output member coupled to a lifting arm of the lifting mechanism, with the lifting arm articulated to a component of a stationary supporting structure for movement of the component between two end positions.

[0003] An adjusting device of this type can be configured for a wide variety of applications. Unlike the rotary drive which normally remains unchanged regardless for which application it is used, the lifting mechanism is configured to suit the application at hand. The adjusting device, involved here, is in particular suitable for applications in which the stationary supporting structure is made of a frame or configured as a frame, and the component being moved is also of

frame-like design and swingably mounted to the supporting structure. The rotary drive is typically a dc gear motor operated with a safety voltage and at an output speed which is fairly small compared to the speed of the rotor of the dc motor.

[0004] The adjusting device is especially used for so-called mass products and thus should be as inexpensive as possible.

[0005] Normally, the rotary drive is secured by a mounting to the stationary parts. This mounting is positioned at an offset to the moving output member of the rotary drive so that the output force of the rotary drive applies a moment upon the mounting. The mounting should therefore be dimensioned accordingly; however the parts of the supporting structure fail to provide the required stability.

SUMMARY OF THE INVENTION

[0006] It is thus an object of the present invention to provide an improved adjusting device, obviating the afore-stated drawbacks.

[0007] In particular, it is an object of the present invention to provide an improved adjusting device with a lifting mechanism which can be suited to the type and operation of the component being moved and is easy and inexpensive to couple to the output member of the rotary drive.

[0011] According to another embodiment of the present invention, the housing of the rotary drive may be supported indirectly by the support beam. This can be implemented, for example, by attaching a fork head with aligned bores to the housing of the rotary drive or forming in the housing wall aligned bores, for passage of the support beam through the bores of the fork head or the bores of the housing wall.

[0012] A particularly simple and operatively safe connection between the output member of the rotary drive and the lifting arm of the lifting mechanism can be realized by form-fittingly connecting the output member of the rotary drive with the lifting arm of the lifting mechanism. In this way, an adjustment of the lifting arm with respect to the output member of the rotary drive is also avoided.

[0013] Suitably, the output member of the rotary drive may be formed by a rotation part with a polygonal bore for snug-fit passage of a crossbar through the

bore, whereby the crossbar has ends which are connected to parallel bars of the swingable components or to the lifting arms of the lifting mechanism. In this manner, a coupling between the parallel lifting arms of the lifting mechanism can be implemented in a most simple manner.

[0014] The rotary drive is suitably mounted in the area of one longitudinal side of the supporting structure to provide superior accessibility. Advantageously, the crossbar may be attached with one rotary drive distal end to a profiled piece which is arranged at the rotary drive facing side of the one lifting arm which is positioned distal to the rotary drive. In this manner, the assembly is convenient and simplified.

[0015] In conventional adjusting devices, the movement between the end positions of the swingable component is restricted by two limit switches, which are mounted within the rotary drive on a strip. Of course, such a configuration is certainly possible also in an adjusting device according to the present invention. However, it is also possible in accordance with another feature of the present invention, to define the end positions of the movable component by at least one stop member which is either provided in the housing of the rotary drive, lifting mechanism or supporting structure. Preferred is a fixed disposition of the stop member so that a moving part of the rotary drive or of the lifting mechanism runs against the stop member in the respective end position. To prevent damage of the drive motor of the rotary drive in the event the motor is not cut immediately

certainly within the scope of the present invention to position the support beams 16, 17 in a vertical orientation in the event some applications require such a disposition.

[0034] In accordance with another variation, as shown in FIG. 3, the housing 13 of the rotary drive mechanism 11 is provided on the side distal to the output member with a fork head 18 or tab. The fork head 18 has aligned bores 2 for snug-fittingly receiving a support member 16 in the form of a rod. As an alternative, the housing 13 may also be formed with two aligned bores for receiving such a rod. Which configuration of the adjusting device 10 is employed is dictated by the application at hand.

[0035] Referring back to FIG. 1, the housing 13 of the rotary drive mechanism 11 is secured to one of the side panels 20 of the slatted frame 1 by a mounting 26, so that the side panel 20 represents the stationary support structure for the adjusting device 10.

[0036] When the dc motor of the rotary drive mechanism 11 is activated, the slanted lifting arm 15 is moved into a horizontal disposition to thereby move the head portion 22 via the swing link 3 and bracket 4 into a slanted disposition, as shown in FIG. 4. Upon further swinging of the lifting arm 15 by the dc motor, the head portion 22 conjointly moves the back portion 19 until reaching an end position in which the back portion 19 also assumes a slanted disposition, as

shown in FIG. 5. Suitably, this end position is defined by a stationary stop member (not shown here), which may project out from the housing 13 or the mounting 26. Lowering of the back portion 19 and the head portion 22 is implemented through reversing the rotation direction of the dc motor.

[0037] Turning now to FIG. 6, there is shown a schematic side view of another embodiment of an adjusting device 10 according to the present invention, mounted to an exemplified slatted frame 1. Parts corresponding with those in FIG. 1 are denoted by identical reference numerals and not explained again. In this embodiment, the slatted frame 1 is devoid of a head portion so that the lifting mechanism 11 can have a simplified configuration. The swingable lifting arms 15 extend underneath in direct contact with the side panels 20 of the swingable back portion 19. Friction between the lifting arms 15 and the underside of the side panels 20 is reduced through the provision of sliders 24 which are made of suitable material known to the artisan and are attached to the free ends of the lifting arms 15.

[0038] When the dc motor of the rotary drive mechanism 11 is activated, the horizontal lifting arms 15 are moved upwardly to thereby move the back portion 19 from the horizontal disposition, shown in FIG. 6, into an intermediate incline position, shown in FIG. 7, as the sliders 24 move along the side panels 20. Upon further swinging of the lifting arms 15 by the dc motor, the back portion 19 moves to the end position, as shown in FIG. 8. Lowering of the back

portion 19 is implemented through reversing the rotation direction of the dc motor. The fully tilted end position of the back portion 19, as shown in FIG. 8 is defined by a stationary stop member 25 which is projects out from the mounting 26 to thereby secure the rotary drive mechanism 11 in proper place on one side panel 20 of the slatted frame 1, so that the lifting arm 15 impacts the stop member 25 when the back portion 19 reaches the end position. Of course, the stop member 25 may be secured also at a different location so that, for example, a side panel of the back portion 19 is intended to strike against the stop member. An attachment upon the housing 13 of the rotary drive mechanism 11 may also be conceivable.

The stationary stop member 25 is so operatively connected to the rotary drive mechanism 11 that the dc motor is cut as soon as the lifting arm 25 strikes against the stop member 25. In order to prevent a risk of damage, it is suitable to incorporate an overload relay (not shown) in the power supply line (not shown) of the rotary drive mechanism. The overload relay opens the motor circuit when the current in the circuit is excessive and exceeds a preset value, thereby providing an overload protection. The provision of a stop member for restricting a movement of the back portion 19 is simple and cost-efficient. Of course, the use of limit switches is also conceivable. Also, the stop member 25 may be resilient so that the increase of current becomes smoother, thereby further protecting the rotary drive mechanism 11.

[0040] As shown in FIG. 9, which is a top view of the adjusting device of FIG. 6, the crossbar 14 for interconnecting the lifting arms 15 is made of two parts and includes the actual crossbar 14 and a profiled piece 27. The rotary drive mechanism 11 is bolted via the mounting 26 to one side panel 20. To simplify the assembly, the profiled piece 27 is secured to the lifting arm 15, which is distal to the rotary drive mechanism 11, and points toward the rotary drive mechanism 11 for receiving the confronting end of the crossbar 14.

[0041] Turning now to FIG. 10, there is shown a schematic side view of yet another embodiment of an adjusting device according to the present invention, mounted to an exemplified chair 29 for adjustment of a footrest 28, shown in stowed end position. Parts corresponding with those in FIG. 1 are denoted by identical reference numerals and not explained again. In this embodiment, the lifting mechanism 12 is used to move the footrest 28 from the stowed end position to a fully extended shown in FIG. 12 and includes a pantograph linkage system 31 for implementing articulated movement of the footrest 28 between the stowed and extended positions. In general, the linkage system 31 is connected between the footrest 28 and the stationary frame of the chair 29 and includes a plurality of links interconnected in a manner generally known to the artisan and not described herein in more detail.

[0042] Persons skilled in the art will understand that the pantographic linkage system 31 is duplicated on the opposite side of the chair 29. For

[0045] What is claimed as new and desired to be protected by Letters Patent is set forth in the appended claims: